

# ROTAMAT® Complete Plant Ro 5HD




## Complete Plant with Hydro Duct

- Well-proven mechanical preliminary treatment equipment
- High grit separation efficiency
- Optional separate grease chamber with grease removal
- Compact, space-saving unit



## ►► Features

The Ro 5HD Complete Plant combines the benefits of both aerated and unaerated grit traps by using a high-performance grit trap with a small overall plan area. The wastewater flows firstly through an inlet screen that retains, washes, compacts and dewateres the solids contained within the flow. The screened wastewater then passes into an aerated grit trap that reduces the settlement of organics within the flow by the action of an aeration system within the grit trap. Grease along with other greasy material are collected in a separate integrated grease trap chamber from where the grease is automatically discharged by a well-proven paddle system. The flow then enters a second unaerated upflow grit trap chamber which contains an integral hydro duct that ensures a directed flow approach **from the bottom** of the chamber with positive and uniform upflow distribution. The flow velocity in the unaerated grit trap chamber is reduced to such an extent that very fine grit is easily and reliably separated. Whilst the separated particles are removed from the grit trap by classifying screws, they are simultaneously being statically dewatered prior to being discharged into a container.



*Schematic drawing of a Ro 5HD Complete Plant*

## ►► Benefits

- Fully integrated screenings separation, washing and dewatering in one system
- Very high levels of grit separation
- Optional separate grease chamber with semi-automatic grease removal system
- Above-ground or underground installation
- Small footprint and space-saving compact design
- Integral emergency overflow in the grit trap
- Optional grit washing system
- Integral emergency by-pass

## ►► Technical information

- Dimensions: see dimension sheet
- Inlet screen: 1 - 10 mm
- Throughput capacity: up to 160 l/s
- Separation efficiency at  $Q_{max}$ : 95% of 0.20 – 0.25 mm grain size
- Completely made of stainless steel (including all classifying screws)
- Maximum corrosion protection through acid treatment in a pickling bath



*Semi-automatic grease removal by means of a paddle system*

**Hans Huber AG**

Maschinen- und Anlagenbau  
Postfach 63 · D-92332 Berching

Phone: + 49 - 84 62 - 201 - 0  
Telefax: + 49 - 84 62 - 201 - 810  
E-mail: [info@huber.de](mailto:info@huber.de)  
Internet: [www.huber.de](http://www.huber.de)

Subject to technical modification

**ROTAMAT®**  
**Complete Plant**  
**Ro 5HD**