

Data sheet SD 7.R

Manhole cover load bearing, round type

HUBER – stainless steel – manhole cover, weatherproof, load bearing up to 15 kN, up to 125 kN, up to 400 kN, round, certificated as burglar–proof, test load as per DIN 1229, completely made of stainless steel. Application areas: for manholes in walking and driving areas.

| Model | Size \varnothing a | Order No. | Inside pass \varnothing b | Frame outside dimensions (without hinge box) \varnothing c | Weight approx. Kg |
|------------------------------------|-------------------------|------------------|--------------------------------|---|----------------------|
| Type A: 15 kN equal 1,5 t (1) | \varnothing 800 | ED 208/15–GR | \varnothing 730 | \varnothing 900 | 54 |
| Type A: 15 kN equal 1,5 t (1) | \varnothing 1000 | ED 201/15–GR | \varnothing 930 | \varnothing 1100 | 72 |
| Type B: 125 kN equal 12,5 t (2) | \varnothing 800 | ED 208/125–GR | \varnothing 700 | \varnothing 900 | 82 |
| Type B: 125 kN equal 12,5 t (2) | \varnothing 1000 | ED 201/125–GR | \varnothing 900 | \varnothing 1100 | 106 |
| Type D: 400 kN equal 40 t (3) | \varnothing 800 | ED 208/400–GR | \varnothing 700 | \varnothing 900 | 92 |
| Type D: 400 kN equal 40 t (3) | \varnothing 1000 | ED 201/400–GR | \varnothing 900 | \varnothing 1100 | 137 |

Ask for further dimensions. All measurements in mm.

(1) Für Grünflächen und Flächen, die nicht als Verkehrsflächen gelten, jedoch gelegentlich begangen werden.

(2) Für Gehwege und vergleichbare Flächen, für PKW–Parkhäuser.

(3) Für Fahrbahnen von Straßen, Parkflächen und befestigte Verkehrsflächen, nicht für fließenden Verkehr geeignet.

| | | | |
|--|--|---|---------------|
| HANS HUBER AG Industriepark Erasbach A1 D – 92334 Berching Germany | Tel. +49 (0)8462 201–0 Fax +49 (0)8462 201–810 info@huber.de www.huber.de www.HansHuberAG.com | Technical leaflet: 16.03.2006 Subject of modification Manhole cover load bearing, round type | SD 7.R |
|--|--|---|---------------|