

Data sheet TT 1.2

Doors with double walls (3), outside, double

Completely made from stainless steel Universally applicable as access to buildings, switch rooms, especially for plants in the field of disposal and supply with average security requirements.

Nominal Size Order No.	Clear wall opening width (2) / height (1)(2)	Clear door opening stock frame width / height	Clear door opening Z-Frame width / height	Frame outside dimension stock frame width / height	Frame outside dimension Z-Frame width / height
1510/2005	1510 / 2005	1370 / 1937	1450 / 1978	1500 / 2035	1621 / 2096
2010/2005	2010 / 2005	1874 / 1937	1955 / 1978	2000 / 2035	2121 / 2096
2010/2130	2010 / 2130	1874 / 2062	1955 / 2103	2000 / 2160	2121 / 2221
2135/2255	2135 / 2255	1995 / 2187	2080 / 2228	2125 / 2285	2246 / 2346

Ask for further dimensions. All measurements in mm.

(1) Named height = bottom edge of lintel to top edge of floor. Shell measure (F) at least must be 35 mm bigger.

(2) with step flashing

Max. size stock-frame: max. width = 2740 mm / max. height = 2890 mm

Max. size z-frame: max. width = 2664 mm / max. height = 2845 mm

(3) Note. A wood finish for the exterior door surface is recommended for installations which are exposed to extreme sunlight to ensure problem-free operation

HANS HUBER AG Industriepark Erasbach A1 D – 92334 Berching Germany	Tel. +49 (0)8462 201-0 Fax +49 (0)8462 201-810 info@huber.de www.huber.de www.HansHuberAG.com	Technical leaflet: 06.03.2006 Subject of modification Doors with double walls (3), outside, double	TT 1.2
--	--	--	---------------