HUBER Solutions for Sludge Treatment

The better wastewater is treated, the more sludge is generated thereby. Primary sludge consists of solids removed from raw wastewater. Secondary sludge consists of biomass generated by biological treatment. Tertiary sludge is generated by advanced chemical/physical treatment.

Most important processes of sludge treatment include:

- Screening for removal of debris and other solids
- Thickening for reducing the sludge amount by concentrating solids
- Hygienizing for inactivation of pathogens
- Dewatering by mechanical water removal
- Drying by thermal water removal (evaporation)
- Incineration by thermal oxidation of organic solids

We offer highly efficient and comprehensive HUBER Solutions for sludge treatment, from mechanical pre-treatment with screens to sludge reuse.

Systems concept



Click on the image to get a detailed, interactive view with additional information and links.

Details

The main waste generated in a municipal waste water treatment plant is the wastewater sludge that is removed from mechanical, biological and chemical wastewater treatment processed.

The amount of sludge depends on the type of treatment, the connected population and population equivalents, and wastewater characteristics. Wastewater characteristics and specific sludge production vary from country to country and from region to region. There is even a difference between urban and rural areas. Sludge production figures range from 20 to 45 kg of dried solids per person per year.

There are several sludge characteristics that have a great influence on the costs of sludge treatment. The water content is very important as it determines the sludge volume and therefore feasibility and costs of transportation and disposal. The solids and water content of sludge depends on the type of sludge (e.g. primary sludge, waste activated sludge, chemical sludge) and the type and quality of its treatment (e.g. sludge digestion) and on the method of sludge thickening and dewatering.

The chemical composition of the sludge also depends on wastewater characteristics and the wastewater treatment method. Of particular importance is the content of heavy metals as their concentration is a limiting factor for land application of biosolids. Despite the fact that land application within the limits set by European biosolids regulation is not only a safe and beneficial reuse of valuable nutrients, there are politically motivated concerns endangering the long-term continuation of land application. The existence of endocrinic substances in biosolids is also an additional concern though these pharmaceutical substances are unlikely to be taken up and incorporated into plants.

European regulations specify that only waste with a volatile solids (organic) content of below 5% may be landfilled. This means the end of the sludge landfilling only the ash from sludge incineration plants may be landfilled. The combination of sludge drying and incineration is about energy neutral. Dried sludge has approximately the same thermal value as brown coal. If dried sludge is incinerated, the generated heat is sufficient for sludge drying.

HUBER offers a virtually complete chain of sludge treatment processes.

Photos

Videos

Animation: HUBER Sludge Dewatering

https://www.youtube.com/watch?v=2bE1Kb5FApc



Animation: Function and components of STRAINPRESS® Sludgecleaner SP

https://www.youtube.com/watch?v=Tb2OoBr7PEs

Video: HUBER Screw Thickener S-DRUM - here at a municipal WWTP

https://www.youtube.com/watch?v=uxjMve6yi50

Video: HUBER Disc Thickener S-DISC - here at a municipal WWTP

https://www.youtube.com/watch?v=3B0yOFFdLyo



Video: HUBER Belt Thickener DrainBelt - here at a municipal WWTP

https://www.youtube.com/watch?v=6pcHf8aJpqQ



Animation: Function and components of new HUBER Screw Press Q-PRESS® 620, 800

https://www.youtube.com/watch?v=t1dSGJYTtCk

Video: HUBER Screw Press Q-PRESS® - here at a municipal WWTP

https://www.youtube.com/watch?v=5VsPNKbkJyA

Video: HUBER Sludge Turner SOLSTICE®

https://www.youtube.com/watch?v=QdWhhrCOkug

Video: Solar Active Dryer SRT at STP Gunstett

https://www.youtube.com/watch?v=JqflpsD16VM

Video: Solar Active Dryer SRT at STP Marktbergl

https://www.youtube.com/watch?v=ZajIn8OGxpk

Animation: HUBER Sludge Turner SOLSTICE® for large quantities of sludge

https://www.youtube.com/watch?v=T-FUbjSzMZE



Animation: HUBER Sludge Turner SOLSTICE®

https://www.youtube.com/watch?v=gOkKQhmA4uM

Sewage Sludge Drying with HUBER Belt Dryer BT

https://www.youtube.com/watch?v=6VTJ1ex10bQ

Video: HUBER Belt Dryer BT for high efficiency sewage sludge drying

https://www.youtube.com/watch?v=PN7G-vk_r3c



Animation: HUBER Disc Dryer RotaDry®

https://www.youtube.com/watch?v=ldLZjLGGx10

ROTAMAT Ltd. t/a HUBER Technology
Units C&D Brunel Park Bumpers Farm Ind. Est.
Chippenham Wiltshire SN14 6NQ
Registered in England No. 2874696 VAT Registration No. 639396393
Telephone: 01249 765000
rotamat@huber.co.uk www.huber.co.uk

A member of the HUBER Group